

# OD View - User's Manual

January 31th, 2012  
rev. 1.1

Photon System Instruments  
[www.psi.cz](http://www.psi.cz)

# 1 General Information

- ODView is Windows XP/Windows 7 application allowing to download protocol data
- before running the application, please make sure that the device is running and connected to the computer

## 2 Data Tab

time	T[C]	L1_680	L1_730	L2_680	L2_730	L3_680	L3_730	L4_680	L4_730	L5_680	L05_730	L6_680	L6_730	L7_680	L7_730	L8_680	L8_730
0 min	25.0	1.80	1.43	1.64	1.39	1.92	1.51	1.61	1.32	1.65	1.34	1.60	1.33	1.74	1.37	1.50	1.26
10 min	25.0	1.81	1.44	1.69	1.42	1.92	1.52	1.66	1.35	1.72	1.38	1.66	1.36	1.77	1.39	1.61	1.32
19 min	25.0	1.81	1.44	1.73	1.44	1.93	1.53	1.72	1.38	1.77	1.40	1.70	1.39	1.80	1.40	1.68	1.36
29 min	24.9	1.81	1.44	1.76	1.45	1.93	1.52	1.75	1.39	1.79	1.41	1.72	1.40	1.80	1.40	1.73	1.39
38 min	25.0	1.81	1.44	1.77	1.46	1.93	1.53	1.78	1.40	1.80	1.41	1.73	1.40	1.80	1.40	1.75	1.40
48 min	24.9	1.82	1.44	1.79	1.47	1.93	1.53	1.79	1.41	1.80	1.41	1.74	1.40	1.80	1.40	1.77	1.41
58 min	24.9	1.82	1.44	1.80	1.47	1.93	1.53	1.81	1.42	1.80	1.42	1.74	1.41	1.80	1.40	1.79	1.42
1.2 h	25.0	1.82	1.44	1.81	1.48	1.93	1.52	1.83	1.43	1.80	1.42	1.74	1.41	1.80	1.41	1.79	1.42
1.3 h	25.0	1.82	1.44	1.82	1.48	1.93	1.52	1.83	1.43	1.80	1.42	1.74	1.41	1.81	1.41	1.80	1.42
1.5 h	25.0	1.82	1.44	1.82	1.48	1.93	1.53	1.84	1.43	1.80	1.42	1.74	1.41	1.80	1.41	1.80	1.42
1.6 h	25.0	1.82	1.44	1.82	1.48	1.93	1.52	1.85	1.43	1.80	1.42	1.74	1.41	1.81	1.41	1.81	1.43
1.8 h	24.9	1.82	1.44	1.83	1.48	1.95	1.53	1.85	1.44	1.80	1.42	1.74	1.41	1.81	1.41	1.81	1.43
2.0 h	24.9	1.82	1.44	1.83	1.49	1.93	1.53	1.85	1.44	1.80	1.42	1.74	1.41	1.81	1.41	1.82	1.43
2.1 h	25.0	1.82	1.44	1.84	1.49	1.93	1.52	1.85	1.44	1.81	1.42	1.74	1.41	1.81	1.41	1.82	1.43
2.3 h	24.9	1.82	1.44	1.83	1.49	1.93	1.52	1.86	1.44	1.81	1.42	1.74	1.41	1.81	1.41	1.82	1.43
136.8 h	24.9	1.76	1.45	1.76	1.49	1.77	1.48	1.70	1.41	1.81	1.46	1.74	1.45	1.64	1.36	1.61	1.38
137.0 h	25.1	1.76	1.45	1.76	1.49	1.77	1.48	1.70	1.40	1.82	1.46	1.74	1.45	1.64	1.36	1.61	1.38
137.1 h	25.0	1.76	1.45	1.75	1.48	1.76	1.48	1.71	1.41	1.81	1.46	1.74	1.45	1.64	1.36	1.61	1.38
137.3 h	25.0	1.75	1.45	1.76	1.49	1.77	1.48	1.70	1.41	1.81	1.46	1.74	1.45	1.65	1.36	1.61	1.38
137.5 h	24.9	1.76	1.45	1.76	1.49	1.77	1.48	1.71	1.41	1.82	1.46	1.74	1.45	1.65	1.36	1.62	1.38
137.6 h	25.1	1.76	1.45	1.75	1.48	1.76	1.48	1.70	1.41	1.81	1.46	1.74	1.45	1.64	1.36	1.62	1.38
137.8 h	24.9	1.76	1.45	1.75	1.48	1.76	1.48	1.70	1.41	1.81	1.46	1.74	1.45	1.64	1.36	1.62	1.38
137.9 h	25.0	1.75	1.45	1.75	1.48	1.76	1.48	1.71	1.41	1.81	1.46	1.74	1.45	1.64	1.36	1.61	1.38
138.1 h	25.0	1.75	1.45	1.76	1.49	1.76	1.48	1.70	1.40	1.82	1.46	1.74	1.45	1.64	1.36	1.62	1.38
138.3 h	25.1	1.75	1.45	1.75	1.49	1.76	1.48	1.70	1.41	1.82	1.47	1.74	1.45	1.64	1.36	1.61	1.38
138.4 h	25.0	1.76	1.45	1.76	1.49	1.76	1.48	1.71	1.41	1.81	1.46	1.74	1.45	1.65	1.36	1.61	1.38
138.6 h	25.0	1.76	1.45	1.75	1.49	1.77	1.48	1.71	1.41	1.81	1.46	1.74	1.45	1.64	1.36	1.61	1.38
138.7 h	25.0	1.75	1.45	1.75	1.49	1.76	1.48	1.71	1.40	1.82	1.46	1.74	1.45	1.64	1.36	1.61	1.38
138.9 h	25.0	1.75	1.45	1.75	1.49	1.76	1.48	1.71	1.41	1.82	1.47	1.74	1.45	1.64	1.36	1.61	1.38
139.1 h	25.0	1.76	1.45	1.75	1.49	1.76	1.48	1.70	1.40	1.81	1.46	1.74	1.45	1.64	1.36	1.61	1.38


### 2.1 Download/Detect

After application launch, detection of the device is started. When successful, label "Download" appears on the button (1). If the connection to MC1000 was not found, the detection can be run again by pressing "Detect" button (1).

After the device is found, select port from the combobox (2) next to the button. If multiple devices found, they are all listed here. Then press "Download" button (1). The OD data download procedure starts, it can take up to few minutes if device memory is full.

When the download is finished, basic information about protocol (3) and few OD measurements (4) are shown.

## 3 Graph Tab



### 3.1 Draw Graph

Select desired combination of Light LEDs by clicking the corresponding checkboxes (1), graph (7) will be updated automatically. Temperature can be added to the graph similarly. There are three group selection/deselection buttons (2) to ease the selection process.

Description field (3) is used as a name of the experiment and also the caption of the graph. Note (4) is generally used to write down some information about experiment setup or progress. Both this fields are exported along with data when "Export to csv" is clicked. They are also saved to the *odview.note* file every time their content changes.

### 3.2 Save Data

Raw data can be saved to comma separated values (.csv) file by clicking "Export to csv" button (5). Csv data format was chosen because it is easily portable and its import is supported by most of the spreadsheet software.

Graph could be saved to bitmap file (\*.bmp) by clicking "Export to Image" button (6).

## **4 Calibration Debug Tab**

This tab serves for factory calibration purposes.

## **5 Revision Changes**

rev 1.1

- page 1 - tab about COM port restrictions obsolete, removed